



AAMA/WDMA/CSA 101/I.S.2/A440-08
TEST REPORT

SELF-FLASHING, THERMALLY BROKEN - SKYLIGHT, WITH INSULATED CURB WITH NAILER- SPECIFICATION:

Self-Flashing, Thermally Broken (dome or pyramid as an option) skylight, as manufactured by ORCA Manufacturing, Inc., Model SFA-TB - 9ISC (NAILER) (6" and 12" curbs available as an option) shall be factory assembled units, each consisting of acrylic domes or pyramids, with .072 extruded glazing sash and with extruded aluminum glazing retaining angle. Each unit will have a built-in evaporative condensation gutter. Insulated curbs shall be of double wall construction of corrosion resistant aluminum connected at top and bottom with thermal barriers. Units shall have a 3" mounting flange for installation to roof deck. Above is of all welded construction.

OSHA FALL PROTECTION COMPLIANT

SFA-TB-9ISCN					
Model	Dimensions (R.O.)	Glazing	Finish	Quantity	Project



TITLE: SELF FLASHING ACRYLIC - THERMALLY BROKEN INSULATED SELF CURB WITH NAILER

Rev. Date	April 18, 2012	Sheet: 1 OF 1
Drawn By	AP	
Rev. By	CRH	Dwg No.
Engineer:	AP	SFA-TB-ISCN 041812

ORCA Manufacturing, inc.
P.O. Box 992
Hurlock, MD 21643
PHONE (800) 776-1539
FAX (410)-943-8245
www.starlightskylights.com