



AAMA 1503-09 THERMAL PERFORMANCE TEST	
1. Condensation resistance factor - Frame (CRF)	32
2. Condensation resistance factor - Glass (CRF)	67
3. Thermal transmittance due to conduction (U-Value)	.43

EXTREME CURB MOUNT-THERMALLY BROKEN - SPECIFICATION:
 Extreme Curb Mount-Thermally Broken, as manufactured by ORCA Manufacturing, Inc., with sealed insulated acrylic pyramidal dome over 16 mm Multiwall Polycarbonate panel (Clear over White standard, Clear over Bronze tint available as an option) in a welded extruded aluminum sash. Each unit will have a built-in evaporative condensation gutter. Finish in bronze or mill, (white gloss enamel as an option).
OSHA FALL PROTECTION COMPLIANT.

Model	Dimensions (F/F)	Glazing	Finish	Quantity	Project
CMA-TB-X-PYR					



TITLE: CURB MOUNT - THERMALLY BROKEN - EXTREME - PYRAMID		
Rev. Date	April 13, 2012	
Drawn By	AP	Sheet: 1 OF 1
Rev. By	CRH	Dwg No.
Engineer:	AP	CMA-TB-X-PYR 041312

ORCA Manufacturing, inc.
 P.O. Box 992
 Hurlock, MD 21643
 PHONE (800) 776-1539
 FAX (410)-943-8245
 www.starlightskylights.com